

**Big Dutchman®****Fan BD-VC130-5-1.50HP-R 41800m³ 400-3-50 assembled/with con**

Article number: 60-25-4060

**Big Dutchman®****Basic data**

Montiert	Mounted
Type	Installation at a wall

Rated values

Phases	3 Ph
Nominal frequency [Hz]	50 Hz
Control	Not controllable

Classification

IP protection rating	IP55
Certifications	CE
Insulation class (DIN EN 60085)	F

Dimensions

Width	1382 mm
Height	1382 mm
Total depth	1275 mm
Diameter	1284 mm
Other dimension	1600 mm

Rated values 50 Hz

Elektrische Nennleistung	1.65 kW
Nominal voltage delta connection	230 V
Nominal voltage star connection	400 V

**Rated values 50 Hz**

Nominal current delta connection	5,2 A
Nominal current star connection	3 A
Speed	580 U/min
Power factor	0.74
Ambient temperature	-25 - 40 °C
Sound power level L _w	89 dB
Sound pressure level L _p	64 dB

Volumetric flow rate 50 Hz

Characteristic curve – 0 Pa	41733 m ³ /h
Characteristic curve – 10 Pa	40328 m ³ /h
Characteristic curve – 20 Pa	38729 m ³ /h
Characteristic curve – 30 Pa	37193 m ³ /h
Characteristic curve – 40 Pa	35570 m ³ /h
Characteristic curve – 50 Pa	33993 m ³ /h
Characteristic curve – 60 Pa	32210 m ³ /h
Characteristic curve – 70 Pa	29415 m ³ /h
Characteristic curve – 80 Pa	27003 m ³ /h
Characteristic curve – 90 Pa	22913 m ³ /h
Characteristic curve – 100 Pa	16625 m ³ /h

Spec. power 50 Hz

Characteristic curve – 0 Pa	33.4 W/(1000m ³ /h)
Characteristic curve – 10 Pa	35.6 W/(1000m ³ /h)
Characteristic curve – 20 Pa	38.6 W/(1000m ³ /h)
Characteristic curve – 30 Pa	41.4 W/(1000m ³ /h)
Characteristic curve – 40 Pa	44.6 W/(1000m ³ /h)
Characteristic curve – 50 Pa	48 W/(1000m ³ /h)
Characteristic curve – 60 Pa	51.7 W/(1000m ³ /h)
Characteristic curve – 70 Pa	58.2 W/(1000m ³ /h)
Characteristic curve – 80 Pa	64.1 W/(1000m ³ /h)
Characteristic curve – 90 Pa	75.3 W/(1000m ³ /h)
Characteristic curve – 100 Pa	101.1 W/(1000m ³ /h)
Characteristic curve – 110 Pa	131.2 W/(1000m ³ /h)