

**Fan incorporable 4E40-Q 5050m³ 230V 220W 1,0A**

Article number: 60-47-7540

**Big Dutchman®****Basic data**

Montiert	Mounted
Thermal protection contact	Yes
Type	Installation in pipe
Weight	8.7 kg

Rated values

Phases	1 Ph
Nominal frequency [Hz]	50 Hz
Control	Triac / Transformer

Classification

IP protection rating	IP55
Certifications	CE
Insulation class (DIN EN 60085)	F
Efficiency rating (ErP)	E20

Rated values 50 Hz

Elektrische Nennleistung	0.22 kW
Nominal voltage single-phase	230 V
Nominal current single-phase	1,0 A
Speed	1430 U/min
Ambient temperature	-25 - 40 °C
Sound power level Lw	75 dB
Sound pressure level Lp	65 dB

**Volumetric flow rate 50 Hz**

Characteristic curve – 0 Pa	5050 m ³ /h
Characteristic curve – 10 Pa	4900 m ³ /h
Characteristic curve – 20 Pa	4750 m ³ /h
Characteristic curve – 30 Pa	4600 m ³ /h
Characteristic curve – 40 Pa	4450 m ³ /h
Characteristic curve – 50 Pa	4300 m ³ /h
Characteristic curve – 60 Pa	4100 m ³ /h
Characteristic curve – 70 Pa	3900 m ³ /h
Characteristic curve – 80 Pa	3550 m ³ /h

Spec. power 50 Hz

Characteristic curve – 0 Pa	43.1 W/(1000m ³ /h)
Characteristic curve – 10 Pa	45.4 W/(1000m ³ /h)
Characteristic curve – 20 Pa	47.6 W/(1000m ³ /h)
Characteristic curve – 30 Pa	50.6 W/(1000m ³ /h)
Characteristic curve – 40 Pa	52.8 W/(1000m ³ /h)
Characteristic curve – 50 Pa	55.6 W/(1000m ³ /h)
Characteristic curve – 60 Pa	58.7 W/(1000m ³ /h)
Characteristic curve – 70 Pa	62.2 W/(1000m ³ /h)
Characteristic curve – 80 Pa	67.9 W/(1000m ³ /h)