

**Big Dutchman®****Fan GF-C92-3 240/420-3-60 T unassembled cone/plastic shutter**

Article number: 82-90-2803

**Basic data**

Montiert

Unmounted

Type

Installation at a wall

Rated values

Phases

3 Ph

Nominal frequency [Hz]

60 Hz

Control

Transformer

Classification

IP protection rating

IP55

Insulation class (DIN EN 60085)

F

Rated values 60 Hz

Elektrische Nennleistung

0.74 kW

Nominal voltage delta connection

240 V

Nominal voltage star connection

420 V

Nominal current delta connection

3,6 A

Nominal current star connection

2,1 A

Speed

810 U/min

Ambient temperature

-25 - 40 °C

Volumetric flow rate 60 Hz

Characteristic curve – 0 Pa

20490 m³/h

Characteristic curve – 10 Pa

19508 m³/h

www.bigdutchman.shop

9/2/2023



Big Dutchman®

Volumetric flow rate 60 Hz

Characteristic curve – 20 Pa	18505 m ³ /h
Characteristic curve – 30 Pa	17287 m ³ /h
Characteristic curve – 40 Pa	15811 m ³ /h
Characteristic curve – 50 Pa	14164 m ³ /h
Characteristic curve – 60 Pa	11967 m ³ /h
Characteristic curve – 70 Pa	9824 m ³ /h

Spec. power 60 Hz

Characteristic curve – 0 Pa	35.9 W/(1000m ³ /h)
Characteristic curve – 10 Pa	38.5 W/(1000m ³ /h)
Characteristic curve – 20 Pa	41.9 W/(1000m ³ /h)
Characteristic curve – 30 Pa	46.2 W/(1000m ³ /h)
Characteristic curve – 40 Pa	51.2 W/(1000m ³ /h)
Characteristic curve – 50 Pa	57 W/(1000m ³ /h)
Characteristic curve – 60 Pa	66.6 W/(1000m ³ /h)
Characteristic curve – 70 Pa	80.4 W/(1000m ³ /h)