

**Fan LPC-12 1 Ph 50/60 Hz 230 V 15,100 m³ 4.2 A for CL-600 T**

Article number: 60-47-3937

**Dimensions**

Width	565.00 mm
Actual weight	14.940 kg

Basic data

Montiert	Mounted
Thermal protection contact	Yes
Type	Installation in pipe
Chimney	600 - CL 600

Rated values

Phases	1 Ph
Nominal frequency [Hz]	50/60 Hz
Control	0-10 V

Classification

IP protection rating	IP54
Certifications	CE
Insulation class (DIN EN 60085)	F
Efficiency rating (ErP)	E15

Rated values 50 Hz

Elektrische Nennleistung	0.8 kW
Nominal voltage single-phase	230 V
Voltage tolerance	-10 - 10 %

**Rated values 50 Hz**

Nominal current single-phase	4,2 A
Speed	1225 U/min
Power factor	0.99
Ambient temperature	-40 - 40 °C
Sound power level L _w	88 dB
Sound pressure level L _p	60 dB

Volumetric flow rate 50 Hz

Characteristic curve – 0 Pa	15100 m ³ /h
Characteristic curve – 10 Pa	14700 m ³ /h
Characteristic curve – 20 Pa	14500 m ³ /h
Characteristic curve – 30 Pa	14100 m ³ /h
Characteristic curve – 40 Pa	13900 m ³ /h
Characteristic curve – 50 Pa	13500 m ³ /h

Rated values 60 Hz

Elektrische Nennleistung	0.8 kW
Nominal voltage single-phase	230 V
Voltage tolerance	-10 - 10 %
Nominal current single-phase	4,2 A
Speed	1225 U/min
Power factor	0.99
Ambient temperature	-40 - 40 °C
Sound power level L _w	88 dB
Sound pressure level L _p	60 dB