

**Fan LPC-13 1Ph 50/60Hz 230V 16,000m³ f/CL-600 T**

Article number: 60-47-3938

**Dimensions**

Length	759.00 mm
Width	531.00 mm
Height	341.00 mm
Actual weight	14.795 kg

Basic data

Montiert	Mounted
Thermal protection contact	Yes
Type	Installation in pipe
Chimney	600 - CL 600

Rated values

Phases	1 Ph
Nominal frequency [Hz]	50/60 Hz
Control	0-10 V

Classification

IP protection rating	IP54
Certifications	CE
Insulation class (DIN EN 60085)	F
Efficiency rating (ErP)	E15

Rated values 50 Hz

Elektrische Nennleistung	0.8 kW
www.bigdutchman.shop	9/1/2023

**Rated values 50 Hz**

Nominal voltage single-phase	230 V
Voltage tolerance	-10 - 10 %
Nominal current single-phase	4,2 A
Speed	1325 U/min
Power factor	0.99
Ambient temperature	-40 - 40 °C
Sound power level L _w	91 dB
Sound pressure level L _p	63 dB

Volumetric flow rate 50 Hz

Characteristic curve – 0 Pa	16000 m ³ /h
Characteristic curve – 10 Pa	15800 m ³ /h
Characteristic curve – 20 Pa	15500 m ³ /h
Characteristic curve – 30 Pa	15200 m ³ /h
Characteristic curve – 40 Pa	14900 m ³ /h
Characteristic curve – 50 Pa	14600 m ³ /h

Rated values 60 Hz

Elektrische Nennleistung	0.8 kW
Nominal voltage single-phase	230 V
Voltage tolerance	-10 - 10 %
Nominal current single-phase	4,2 A
Speed	1325 U/min
Power factor	0.99
Ambient temperature	-40 - 40 °C
Sound power level L _w	91 dB
Sound pressure level L _p	63 dB