

**Mot-g 0.18 220/380 60 3 12.2U SK200-63L/4 M6 shaft 25x60**

Article number: 90-00-3784

**Dimensions**

Length	431.00 mm
Width	187.00 mm
Height	203.00 mm
Actual weight	19.027 kg

Basic data

Running mode	S1 S1-S10
Motor size	63
Gear type	Spur gear
Gear design	Foot version
Norm	IEC60034
Weight	19 kg

Rated values

Phases	3 Anzahl
Frequency	60 Hz
Pole pair	4
Type of connection	Star/Delta
Permiss. ambient temp. during operation	-20 - 40 °C
Kabel Motor	4 adrig

Classification

Wirkungsgradklasse	IE1 IE1-IE5
--------------------	-------------



Classification

IP protection rating	IP55 IP
Insulation class	F
Certifications	CE

Dimensions

Output shaft length	60 Länge mm
---------------------	----------------

Rated values 60 Hz

Nominal power	0,18 kW
Nominal voltage delta connection	220 V
Nominal voltage star connection	380 V
Current consumption delta connection	0,95 A
Current consumption star connection	0,55 A
Anlaufstrom I_a/I_n	3 Faktor
Power factor	0.75
Efficiency	59
Motor speed	1625 r/min
Gear speed	12,2 r/min