



Mot-g 0.75 230/400/50 17r RF37 DRN80M4/RS VW25 RLS

Article number: 90-00-3928



Dimensions

Length	553.00 mm
Width	215.00 mm
Height	168.00 mm
Actual weight	24.386 kg

Basic data

Running mode	S1 S1-S10
Gear design	Flange version
Weight	24.8 kg

Rated values

Phases	3 Anzahl
Frequency	50/60 Hz
Controllable by	Frequenzumformer
Permiss. ambient temp. during operation	-10 - 40 °C

Classification

Wirkungsgradklasse	IE2 IE1-IE5
IP protection rating	IP54 IP
Certifications	CE



Dimensions

Output shaft length

50 Länge
mm

Rated values 50 Hz

Nominal power	0,75 kW
Nominal voltage delta connection	220-242 V
Nominal voltage star connection	380-420 V
Current consumption delta connection	3,05 A
Current consumption star connection	1,75 A
Power factor	0.79
Efficiency	81
Gear speed	17 r/min

Rated values 60 Hz

Nominal power	0,75 kW
Nominal voltage delta connection	254-277 V
Nominal voltage star connection	440-480 V
Current consumption delta connection	2,65 A
Current consumption star connection	1,52 A
Power factor	0.76
Efficiency	82.5
Gear speed	21 r/min