

**Fan FC035-4EQ 3460m³ 230V 157W 1.0A**

Article number: 60-47-9135

**Dimensions**

Length	487.00 mm
Width	485.00 mm
Height	176.00 mm
Actual weight	8.127 kg

Basic data

Montiert	Mounted
Thermal protection contact	Yes
Type	Installation at a wall

Rated values

Phases	1 Ph
Nominal frequency [Hz]	50 Hz
Control	Frequency converter (with all-pole sinusoidal filter) / Transformer / Triac

Classification

IP protection rating	IP54
Certifications	CE
Insulation class (DIN EN 60085)	F
Efficiency rating (ErP)	E15

Dimensions

Width	435 mm
Height	485 mm

**Dimensions**

Total depth	177 mm
Diameter	375 mm

Rated values 50 Hz

Elektrische Nennleistung	0.16 kW
Nominal voltage single-phase	230 V
Nominal current single-phase	0,75 A
Speed	1370 U/min
Ambient temperature	-25 - 40 °C
Sound power level L _w	69 dB
Sound pressure level L _p	44 dB

Volumetric flow rate 50 Hz

Characteristic curve – 0 Pa	3466 m ³ /h
Characteristic curve – 10 Pa	3322 m ³ /h
Characteristic curve – 20 Pa	3182 m ³ /h
Characteristic curve – 30 Pa	3047 m ³ /h
Characteristic curve – 40 Pa	2916 m ³ /h
Characteristic curve – 50 Pa	2775 m ³ /h
Characteristic curve – 60 Pa	2532 m ³ /h
Characteristic curve – 70 Pa	2260 m ³ /h

Spec. power 50 Hz

Characteristic curve – 0 Pa	45.5 W/(1000m ³ /h)
Characteristic curve – 10 Pa	48.8 W/(1000m ³ /h)
Characteristic curve – 20 Pa	51.8 W/(1000m ³ /h)
Characteristic curve – 30 Pa	54.7 W/(1000m ³ /h)
Characteristic curve – 40 Pa	58.2 W/(1000m ³ /h)
Characteristic curve – 50 Pa	61.1 W/(1000m ³ /h)
Characteristic curve – 60 Pa	67.3 W/(1000m ³ /h)
Characteristic curve – 70 Pa	75.2 W/(1000m ³ /h)