

**Big Dutchman®****Fan BD-VC140-3-2.00HP EVO 53700mÂ³ 400-3-50 assemb w/cone w/F**

Article number: 60-25-4062

**Big Dutchman®****Basic data**

|                            |                           |
|----------------------------|---------------------------|
| Primary stamping           | 1 â€” (50 Hz)             |
| Wire mesh guard            | Suction side              |
| Montiert                   | Mounted                   |
| Thermal protection contact | No                        |
| Type                       | Installation at a wall    |
| Weight                     | Installation at a wall kg |

**Rated values**

|                        |                     |
|------------------------|---------------------|
| Nominal frequency [Hz] | 50 Hz               |
| Control                | Frequency converter |
| Type of connection     | Star                |

**Classification**

|                                  |      |
|----------------------------------|------|
| IP protection rating             | IP55 |
| Certifications                   | CE   |
| Insulation class (DIN EN 60085)  | F    |
| Efficiency rating (ErP)          | E20  |
| IE classification (IEC 60034-30) | IE3  |

**High&Low**

|                 |            |
|-----------------|------------|
| Neg. Pressure 1 | 0-20       |
| Low: Volt       | 0-20 V     |
| Low: RPM 1      | 0-20 U/min |
| High: RPM 1     | 0-20 U/min |



## High&Low

|                 |             |
|-----------------|-------------|
| Neg. Pressure 2 | 20-40       |
| Low: Volt 2     | 20-40 V     |
| Low: RPM 2      | 20-40 U/min |
| High: RPM 2     | 20-40 U/min |
| 0 PA - Low      | 20-40 m3/h  |
| 0 PA - High     | 20-40 m3/h  |
| 10 PA - Low     | 20-40 m3/h  |
| 10 PA - High    | 20-40 m3/h  |
| 20 PA - Low     | 20-40 m3/h  |
| 20 PA - High    | 20-40 m3/h  |
| 30 PA - Low     | 20-40 m3/h  |
| 30 PA - High    | 20-40 m3/h  |
| 40 PA - Low     | 20-40 m3/h  |
| 40 PA - High    | 20-40 m3/h  |